

IPZ STOCK GmbH							
Lieferprogramm Brennröhre / Kernlanzen / Oxygen Lanzen							
					LP: Lieferprogramm		
1. Brennröhre, ungefüllt					LG: Lagerprogramm		
IPZ-Art.	Zoll	AD	WS	Länge	o/o*	m/m*	
SG40FF-6	1/8"	10,2	2,0	HL 6 m	LP	-	
GHR-815	1/4"	13,5	1,5	HL 6 m	LG	-	
SG40FF-82000	1/4"	13,5	2,3	HL 2,0 m	LG	-	
SG40FF-82700	1/4"	13,5	2,3	HL 2,7 m	LG	-	
SG40FF-83000	1/4"	13,5	2,0/2,3	HL 3 m	LG		
SG40FF-84000	1/4"	13,5	2,3	HL 4 m	LG	LP	
SG40FF-8	1/4"	13,5	2,0/2,3	HL 6 m	LP		
SG40FF-8MM	1/4"	13,5	2,3	HL 6 m		LG	
SG40FF-103000	3/8"	17,2	2,0 / 2,3	HL 3 m	LG		
SG40FF-103500	3/8"	17,2	2,0 / 2,3	HL 3,5 m	LP		
SG40FF-104000	3/8"	17,2	2,0 / 2,3	HL 4 m	LG		
SG40FF-104800	3/8"	17,2	2,0	HL 4,8 m	LP		
SG40FF-105000	3/8"	17,2	2,0/2,3	HL 5,0 m	LP		
SG40FF-107000 L	3/8"	17,2	2,0	HL 7 m	LG		
SG40FF-10	3/8"	17,2	2,0/2,3	HL 6 m	LG	LP	
SG40FF-103000MM	3/8"	17,2	2,3	HL 3 m		LP	
SG40FF-104000MM	3/8"	17,2	2,0 / 2,3	HL 4 m		LG	
SG40FF-153000	1/2"	21,3	2,3 / 2,6	HL 3 m	LG	LP	
SG40FF-154000	1/2"	21,3	2,3 / 2,6	HL 4 m	LG		
SG40FF-157000	1/2"	21,3	2,3	HL 7 m	LP		
SG40FF-15	1/2"	21,3	2,3/2,6	HL 6 m	LG	LP	
SG40FF-154000MM	1/2"	21,3	2,3 / 2,6	HL 4 m		LG	
SG40FF-15MM	1/2"	21,3	2,3/2,6	HL 6 m		LG	
SG41FF-15 H	1/2"	21,3	3,2	HL 6 m	LG		
SG40FF-205000	3/4"	26,9	2,3/2,6	HL 5 m	LG	LP	
SG40FF-20	3/4"	26,9	2,6	HL 6 m	LG		
SG40FF-20MM	3/4"	26,9	2,3/2,6	HL 6 m		LG	
SG40FF-25	1"	33,7	3,2	HL 6 m	LP	LP	
SG40FF-325000	1 1/4"	42,4	3,2	HL 5 m	LP		
SG40FF-32	1 1/4"	42,4	3,2	HL 6 m	LP	LP	
Weitere Abmessungen/Ausführungen/Längen auf Anfrage							
					*o/o	OHNE Gewinde, OHNE Muffe	
					*m/m	MIT Gewinden, MIT Muffe	
2. Kernlanzen, gefüllt							
IPZ-Art.	Zoll	AD	Länge	Füllung			
CATOX-103000	3/8"	17,2	3 m	2,6 m	LP	LP	
CATOX-103500	3/8"	17,2	3,5 m	3,1 m	LG	LP	
CATOX-105000	3/8"	17,2	5 m	4 m	LP		
CATOX-106000MM	3/8"	17,2	6 m	6 m	LP	LP	
CATOX-153000	1/2"	21,3	3 m	2,5 m	LP		
CATOX-153500	1/2"	21,3	3,5 m	2,5 m	LP		
CATOX-154000	1/2"	21,3	4 m	3,5 m	LP		
CATOX-154000	1/2"	21,3	4 m	3 m	LP		
CATOX-156000	1/2"	21,3	6 m	5,5 m	LP		
Weitere Abmessungen/Ausführungen/Längen auf Anfrage							
3. Oxygen Lanzen, alitiert und keramisch beschichtet							
	Zoll	AD	Länge	P/E*	T/C*	UT/C*	
OXYL-82750	1/4"	13,6	2,75 m	LP	LP	LP	
OXYL-85500	1/4"	13,6	5,50 m	LP	LP	LP	
OXYL-102750	3/8"	17,2	2,75 m	LP	LP	LP	
OXYL-105500	3/8"	17,2	5,50 m	LP	LP	LP	
OXYL-152750	1/2"	21,3	2,75 m	LP	LP	LP	
OXYL-155500	1/2"	21,3	5,50 m	LP	LP	LP	
OXYL-202750	3/4"	26,5	2,75 m	LP	LP	LP	
OXYL-205500	3/4"	26,5	5,50 m	LP	LP	LP	
OXYL-252750	1"	33,7	2,75 m	LP	LP	LG	
OXYL-255500	1"	33,7	5,50 m	LP	LP	LG	
OXYL-322750	1 1/4"	42,4	2,75 m	LP	LP	LP	
OXYL-325500	1 1/4"	42,4	5,50 m	LP	LP	LP	
OXYL-402750	1 1/2"	48,3	2,75 m	LP	LP	LP	
OXYL-405500	1 1/2"	48,3	5,50 m	LP	LP	LP	
					P/E*	OHNE Gewinde, OHNE Muffe	
					T/C*	MIT Gewinden, MIT Muffe	
					UT/C*	einseitig mit Presskupplung	
Stand 01.01.2019-WS							